

TSC

The Smarter Choice.



TTP-247 SERIES – Desktop Thermal Transfer Bar Code Printer A NEW STANDARD FOR VALUE IN THE INDUSTRY!



KEY FEATURES

- Up to 177.8 mm (7") per sec. print speed
- 4 MB Flash memory and 8 MB SDRAM memory
- SD Flash memory expansion up to 4 GB
- User-friendly clamshell design
- Label gap sensor & full-range adjustable black mark sensor
- Parallel, serial & USB 2.0 interfaces standard
- Main board integrated with internal Ethernet (factory option)
- Label capacity up to 214 mm (8.4") OD
- Ribbon capacity up to 300 m (984')
- TSPL-EZ™ firmware for plug-n-play ease
- Optional peel-off module, cutter module, Bluetooth module, stand-alone keyboard and scanner

APPLICATIONS

- Business/Office
- Product Marking
- Compliance Labeling
- Asset Tracking
- Document Management
- Shelf-Labeling
- Shipping/Receiving
- Specimen Labeling
- Inventory Control
- Patient Tracking

TTP-247 SERIES – Desktop Thermal Transfer Bar Code Printer

| PRINTER MODEL | TTP-247 | TTP-345 |
|-------------------------------|--|-----------------------------|
| Resolution | 8 dots/mm (203 DPI) | 12 dots/mm (300 DPI) |
| Printing method | Thermal Transfer & Direct Thermal | |
| Max. print speed | 178 mm (7")/second | 127 mm (5")/second |
| Max. print width | 108 mm (4.25") | 106 mm (4.17") |
| Max. print length | 2,286 mm (90") | 1,016 mm (40") |
| Enclosure | Double-walled plastic | |
| Physical dimension | 213 mm (W) x 188 mm (H) x 314 mm (D) 8.39" (W) x 7.40" (H) x 12.36" (D) | |
| Weight | 2.8 kg (6.17 lbs) | |
| Label roll capacity | 127 mm (5") OD | |
| Ribbon | 300 m long, max. OD 67 mm, 1" core (ink coated outside) | |
| Ribbon width | 40 mm ~ 110 mm (1.6" ~ 4.3") | |
| Processor | 32-bit RISC CPU | |
| Memory | <ul style="list-style-type: none"> • 4 MB Flash memory • 8 MB SDRAM • SD card reader for Flash memory expansion, up to 4 GB | |
| Interface | <ul style="list-style-type: none"> • USB 2.0 • RS-232 • Centronics • Internal Ethernet, 10/100 Mbps (factory option) • Bluetooth (user option) | |
| Power | External universal switching power supply <ul style="list-style-type: none"> • Input: AC 100-240V, 2.5A, 50-60Hz • Output: DC 24V, 3.75A, 90W | |
| Operation switch, button, LED | 1 power switch, 1 feed button & 1 LED (3 colors: green, amber & red) | |
| Sensors | <ul style="list-style-type: none"> • Transmissive gap sensor • Black mark reflective sensor (position adjustable) • Ribbon end sensor • Head open sensor | |
| Internal fonts | <ul style="list-style-type: none"> • 8 alpha-numeric bitmap fonts • Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font | |
| Bar code | <ul style="list-style-type: none"> • 1D bar code Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11 • 2D bar code PDF-417, Maxicode, DataMatrix, QR Code, Aztec | |
| Font and barcode rotation | 0, 90, 180, 270 degree | |
| Printer language | TSPL-EZ™ | |
| Media type | Continuous, die-cut, black mark, fan-fold, notched (outside wound) | |
| Media width | 20 ~ 112 mm (0.78" ~ 4.4") | |
| Media thickness | 0.06 ~ 0.19 mm (2.36 ~ 7.48 mil) | |
| Media core diameter | 25.4 ~ 76.2 mm (1" ~ 3") | |
| Label length | 10 ~ 2,286 mm (0.39" ~ 90") | 10 ~ 1,016 mm (0.39" ~ 40") |
| Environment condition | Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing | |
| Safety regulation | FCC Class B, CE Class B, C-Tick Class B, UL, CUL, TÜV/Safety, CCC | |
| Environmental concern | Comply with RoHS, WEEE | |
| Accessories | <ul style="list-style-type: none"> • Windows labeling software CD disk • Quick start guide • USB cable • Power cord • External universal switching power supply • Label spindle, fixing tab x 2, 1.5" core adapter x 2 • Ribbon spindle x 2 • Ribbon paper core | |
| Limited warranty | <ul style="list-style-type: none"> • Printer: 1 years • Print head: 25 km (1 million inches) or 12 months which comes first • Platen: 50 km (2 million inches) or 12 months which comes first | |
| Factory options | <ul style="list-style-type: none"> • Internal Ethernet interface (10/100 Mbps) • Real time clock | |
| Dealer options | <ul style="list-style-type: none"> • Peel-off module • Guillotine cutter (full cut or partial cut) | |
| User options | <ul style="list-style-type: none"> • Bluetooth module (serial interface) • External roll mount, media OD. 214 mm (8.4") on a 1" or 3" core • 3" core label spindle • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard | |



CORPORATE HEADQUARTERS

TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tscprinters.com

LI ZE PLANT

TSC Auto ID Technology Co., Ltd.
Tel: +886 3 990 6677
E-mail: apac_sales@tscprinters.com

AMERICAS

TSC Auto ID Technology America Inc.
Tel: +1 657 258 0808
E-mail: americas_sales@tscprinters.com

MEXICO

TSC Mexico Representative Office
Tel: +52 (33) 3165 7379
E-mail: americas_sales@tscprinters.com

BRAZIL

TSC Brazil Representative Office
Tel: +55 (11) 99597 8098
E-mail: americas_sales@tscprinters.com

EMEA

TSC Auto ID Technology EMEA GmbH
Tel: +49 (0) 8106 37979 00
E-mail: emea_sales@tscprinters.com

RUSSIA

TSC Auto ID Technology EMEA GmbH
Tel: +7 495 249 9017
E-mail: emea_sales@tscprinters.com

MIDDLE EAST

TSC Auto ID Technology ME Ltd, FZE
Tel: +971 4 2533 069
E-mail: emea_sales@tscprinters.com

ASIA PACIFIC

TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tscprinters.com

CHINA

Tianjin TSC Auto ID Technology Co., Ltd.
Tel: +86 22 5981 6661
E-mail: apac_sales@tscprinters.com

TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
© 2017 TSC Auto ID Technology Co., Ltd.
Product models and Specifications are subject to change without notice.
Contact your TSC sales representative for specific information.