



SCANLIFETM

Thermal Receipt Printer


A260H

- Multiple interface connections, auto-cutter, wall mountable.
- Support both 58/80mm width paper.(U+Lan, U+Serial+Lan)
- Support page mode (USB+Lan)
- Support QR Code.
- Support Windows, Linux, Android, iOS, OPOS, and MacOS



A260H

Thermal Receipt Printer



Model	A260H
Printing method	Direct thermal
Printing speed	230 mm/s
Paper width	80mm
Printing Width	72mm
Column capacity	576 dots/line or 512 dots/line
Interface	USB+Lan
Line spacing	3.75mm(Adjustable by commands)
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) , Font B:1.1×2.1mm(9×17 dots) Simplified/Traditional Chinese: 3.0×3.0mm(24×24 dots)

Barcode Character	
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese)/ PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran / WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)
1D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR CODE
Input buffer	128 Kbytes
NV Flash	256 Kbytes

Power	
Power adaptor Input	AC 110~240V, 50~60Hz
Printer Input	DC 24V / 2.5A
Cash drawer	DC 24V / 2.5A

Physical characteristics	
Weight	0.89 Kg
Dimensions	170*130*125mm

Environmental Requirements	
Work environment	Temperature (0~45℃), humidity(10~80%)
Storage environment	Temperature(-10~60℃), humidity(10~90%)

Reliability	
Auto cutter	Partial
Cutter life	1.5 million cuts
Printer head life	150 Km

Software	
Emulation	ESC/POS
Driver	Windows/JPOS/Linux/OPOS/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS, Android, Windows

