




POCKET 2D WIRELESS BARCODE SCANNER

SL-6200 R

- Don't need any driver, plug and play.
- Read 1D and 2D code on screen and paper.
- Super battery capacity is up to 1500mAh.
- Charge time is 3 hours and continuous scanning time is 24hours.
- Support double firmware upgrade online: wireless and decoder.
- Communication model: 2.4G, bluetooth and typeC cable.
- Communication distance(open air) : 2.4G:100meters,Bluetooth: 40meters.
- Smart body, unique and ergonomic design, comfortable operating sense.
- Three LED indicator : Green(decoder light) Red(charge light), Blue(Connection success).

APPLICATION

Mainly used in business, warehousing, express delivery, some industries etc.



SL-6200 R TECHNICAL SPECIFICATION

OS Windows / iOS / Android	Image Sensor CMOS	Image(Pixels) 1280(H)*800 (V)pixels	light source Aiming: 625 nm LED; illumination:4000K LED	Scan Mode Handhand (Manual) / Handfree (Automatic)
FPS 60fps/s	Scan accuracy ≥ 4mil@ Code39	Print Contrast ≥ 20%	Visual Indicator Red, blue and green LED lights Buzzer , motor vibration	Transmission Range 2.4G:50m; Bluetooth HID/BLE/ SPP: 40m(in open air)
Scan Angle Elevation angle 65° Tilt angle 30° Declination 55°	Field of view 34° horizontal, 28° vertical	Work frequency 2.400GHz-2.480GHz ISM	Dimension L x W x H 135*51*40(mm)	Weight 104g
Case Material ABS+PC, TPU	Memory Capacity 150000 EAN 13 BARCODES	Power parameter Input Voltage: 5VDC±5% Working current: 1000mA	Firmware Update Computer online upgrade	Scan distance 40-200mm@UPC/EAN13mil PCS=90%; 20-250mm@QR 20mil PCS=100%
Cable Standard 1.0M straight (Typec)	Paired Mode one to one	Battery Parameters Battery Capacity: 1500mAh Charge Mode: Type-C cable charge Charge time: 4-5h Working time: 8h (Continuous scan)	Safety regulations CE (EN 55032:2015; EN 55035:2017), ROHS, BIS EN62368-1:2014+A11:2017 FCC PART 15 CLASS B	Environmental parameters Operating Temperature: -20°C--+ 60°C Working Humidity: 5% to 95% relative humidity, non-condensing Storage Temperature: -40°C--+70°C Electrostatic protection: ±8 kV (Direct discharge) Ambient brightness: 0-100,000Lux Drop Resistance : 2M IP: IP52

Barcodes Supported

- 1D: UPC/EAN/JAN,UPC-A & UPC-E,EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128 & EAN 128,Code 93, Interleaved 2 of 5 (ITF),Addendum 2 of 5, IATA Code,MSI/Plessy, China Postal Code,Code 32 (Italian Pharmacode), etc.
- 2D: QR Code, Data Matrix, PDF417, Aztec, Maxicode, Dotcode, GS1 DataBar stack, etc.

